XS43Z5A


Truck-mounted Concrete Boom Pump




Main Features

- Assembly on standard 4 axles chassis
- 5 sections placing boom, “RZ” folding system, FEM designed
- Fully hydraulic outrigger controls on both sides of the truck
- Front 2 levels X outrigger and swing-out rear outriggers
- Pumping unit with open hydraulic circuit
- Electrically controlled hydraulic reversing
- MPS (Micro Pressure Shock) reversing buffering technology
- S valve / Rock valve
- Large diameter slide valve with casting oil passage
- Intelligent electrical control system
- Remote / Manual control method for boom and pumping unit
- Centralized lubrication system for pumping unit
- Piston automatic return technology, easy to replace piston
- Main hydraulic pump overload protection technology
- Engine overload protection technology
- Engine low-speed protection technology
- Anti-tipping safety protection technology
- Lights system

Operation range




360°
7.95m
9.00m
9.70m
9.70m
120°
5.09m
5.78m

Main technical parameters

1. Pumping unit technical data

Item		Parameters
Theoretical output (high/low pressure)	m^3/h	170
Delivery pressure	MPa	8
Maximum aggregate diameter	mm	≤40
Concrete cylinder(diameter×stroke)	mm	Φ260×2000
Filling height	mm	1540
Hopper capacity	L	600
Hydraulic circuit		Open
Transfer tube		S valve / Rock valve
Maximum tube swing time per min		25~27

2. Placing boom technical data

Item			Parameters
Max. vertical reach		m	42.1
Max. horizontal distance (from center of slewing axis)		m	37.3
Reach depth		m	29
Pipeline diameter		mm	125
Section numbers			5
1st section unfolding angle			90°
2nd section unfolding angle			180°
3rd section unfolding angle			180°
4th section unfolding angle			230°
5th section unfolding angle			200°
Rotating angle of the placing boom			±360°
Stabilizer span	Longitudinal span	mm	9700
	Front stabilizer transverse span	mm	7950
	Rear stabilizer transverse span	mm	9000

3. Technical data for travel

Chassis brand	**SINOTRUK**
Chassis model	SITRAK ZZ5446V456ME1
Overall dimensions (L×W×H)	12385×2540×4000
Overall weight	35800kg
Axle numbers	4
Wheelbase mm	1950+4500+1400
Tire	385/65 R22.5（20PR），315/80 R22.5（18PR）
Engine Model	MC11.44-50
Max. Power	440HP
Displacement of Engine	10.518L
Emission standard	Euro V / Euro Ⅲ

Technical data and characteristics subject to modifications without notice

XUZHOU XCMG SCHWING CO., LTD
No.29 Taoshan Rd, Xuzhou, Jiangsu, China
Tel: +86 516 83111590
Fax: +86 516 87892035
www.xcmg.com
© by XCMG | All rights reserved